

# Allflex Livestock Intelligence AWR250 Stick Reader

Allflex Livestock Intelligence Stick Readers are high-performance mobile devices for fast reading of high volumes of electronic identification (EID) tags. Ideal for larger groups and herds of animals, our Stick Readers provide outstanding reading performance, combined with long-lasting batteries, robust design, unique data collection features, and extended connectivity options.

The Allflex AWR250 Stick Reader is a highly economical, yet powerful solution for quickly and reliably reading the EID tags of large numbers of animals, and for managing animal events.



- **Advanced management** – Supports full event management, with large memory allowing storage of up to 100,000 records in groups. Easy upload and download of data, along with the possibility to export data to Excel or management software.
- **Broad connectivity** – Comprehensive reading capabilities include all types of HDX and FDX-B transponders, ear tags, and bolus. Bluetooth and USB interfaces are included as standard, and a revolutionary magnetic plug facilitates USB connectivity. Unique online mode and connectivity with iPhone and Android apps allow mobile data management.
- **Easy and comfortable use** – Lightweight, ergonomically designed readers with a durable casing. The large, backlit, color display enables efficient reading of identification and other scanned data. The reading process is easily controlled, even in noisy environments, with the help of LED indicators, a vibrating motor, and loud, operation-specific sounds.

## Allflex AWR250 Stick Reader – Specifications

Frequency	134.2 kHz
Transponder types	HDX and FDX-B compatible (ISO 11784 / 11785)
Read range	Approximately 25 cm / 9.84 in with an HDX or FDX-B transponder of $\varnothing$ 30 mm / 1.18 in
Synchronization	Wireless synchronization allows operation with other readers in close vicinity according to ISO24631-2
Interfaces	USB (virtual COM port or mass storage device) Class 1 Bluetooth module v4.1 Dual mode: Classic (SPP, HID), BLE
Memory	8 GB (100,000 records) 25 tasks with 10,000 records each
Power supply	Integrated Li-ion battery 3.4 Ah (12.6 Wh) Internal charging via USB in max. 4 hours with Allflex supplied PSU
Display	61 mm / 2.4 in TFT (65K colors)
Keypad	7-button directional pad including 'OK' button and two soft keys
Signals	2 status LEDs above the display, audio speaker, and vibrating mode
Operating temperature	-20°C to 60°C / -4°C to 140°F
Storage temperature	-20°C to 60°C / -4°C to 140°F
Charging temperature	0°C to 45°C / 32°C to 113°F
Protection level	IP65 water resistant
Dimensions	L x W x H: 650 mm x 85 mm x 42 mm / 25.6 in x 3.3 in x 1.6 in
Weight	≈ 620gr / 21.87 oz

[www.allflex.global](http://www.allflex.global) | [info@allflex.global](mailto:info@allflex.global)

Allflex Livestock Intelligence, part of MSD Animal Health, is the world leader in the design, development, manufacturing and delivery of solutions for animal identification, monitoring and traceability. Our solutions empower farmers to act in a timely manner, to safeguard their animals' health, while achieving optimal production outcomes for a healthy food supply.

Through its commitment to the Science of Healthier Animals®, MSD Animal Health offers veterinarians, farmers, pet owners and governments one of the widest ranges of veterinary pharmaceuticals, vaccines and health management solutions and services. MSD level VfrRjtyxyj Animal Health is dedicated to preserving and improving the health, well-being and performance of animals and the people who care for them.

Copyright© 2020 SCR Engineers Ltd., subsidiary of Merck & Co., Inc., Kenilworth, New Jersey, U.S.A. The information contained herein is subject to change without notice. The only warranties for SCR's products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. SCR shall not be liable for technical or editorial errors or omissions contained herein.